

LIGHT/ADJ (A Key) ———



———— (B Key) MODE

A . Features

- 3.5 Digits LCD Display, Display Hour ,Minute ,Second ,Month and Day .

B . Operational Manual

1. At any state ,press A key EL backlight for 3s .
2. At time setting mode ,press A key to activate auto advance function.
3. press A key once displaying Date ;twice displaying Second , Press A key again to return to Real Time mode .
4. TIME SETTING
 - Press B key twice to entry Time Setting mode ,select item in turn as following :
Month → Day → Hour → Minute
 - Press A key to adjust the flashing item
 - Press B key to confirm

C. Specifications

- Module Size : 20*17mm
- Module Thickness (include buzzer) : 7.10mm
- Operational Temperature Range : -10℃~60℃
- Operational Voltage : 1.5V
- Accuracy : ±90sec/month
- Battery Code : V391MF (Capability: 42mAh)
- static average current : ≤1.59u A (static maximum current : 2.5uA)
- EL lighten average current : ≤6.74m A (ELlighten maximum current : 10.0mA)
- Battery life : ≥18 month(Japan Lithium)

Under the following conditions:(4 backlight operation (3 seconds) perday .)

	Prepared	Checked	Approve
Name	冯碧颜	徐治中	宋检望
Date	11/04/19	11/04/19	11/04/19